

KI 2600XL / 9600XL Series

Large Area Detector Power Meter / Radiometer

Optical Test Applications

- Testing optical power, attenuation & continuity
- Duplex, ribbon & POF fiber
- Fiber bundles & free space
- Unusual fiber optic connectors
- Active Area to 5 mm diam or 3.5 x 7 mm
- Power from -70 dBm / 100 pW to + 33 dBm / 2 W
- Wavelength range 350 – 1700 nm



Revision 21

The KI 2600XL & KI 9600XL series Optical Power Meters / Radiometers have large area optical detectors. Typical test applications include specialty fiber optic or free space systems employing multi fiber connectors such as MPO/MT/MTP and MTRJ, large core fiber such as POF, fiber bundles, and high-power pump lasers.

Up to 1% traceable accuracy, ease of use and high availability combine to achieve superior measurement confidence.

Detector & calibration options cover a wide range of optical connectors, fiber types, wavelengths and power levels.

Since these meters are ideal for both free space & fiber applications, they are ideal traceable transfer standards for calibrating fiber optic laboratory equipment.

For KI 2600XL, powerful KITS software provides a practical logging / acquisition / reporting environment straight out of the box.

Features

- 5 mm diameter Ge, InGaAs & Si detectors
- 7 x 3.5 mm Ge detector
- 2 mm diameter high power InGaAs & Ge detectors
- Very long battery life
- Industry standard screw-on connector adaptors
- Calibrations at 9 – 28 wavelengths
- KI 2600 external power / charger via micro USB
- KI 2600 memory with text, timestamp, USB dump, KITS™ data logging / reporting software
- Test Tone Detection
- Max / min recording
- Compact, rugged and light weight
- Sunlight readable display
- ISO 17025 traceable calibration certificate
- 3 ~7 years warranty
- 3 years recommended calibration cycle
- Made in Australia

KI 2600XL / 9600XL Series – Large Area Detector Power Meter / Radiometer

The XL series Large Area Detector Optical Power Meters measure absolute and relative light levels. High accuracy and simplicity of use make them ideal for field and laboratory use.

The industry standard 7/8" 28 TPI screw on connector interface can be equipped with almost any connector style.

Operational savings result from up to 1000-hour battery life, and no range changing delays.

The meters display mW, µW, nW, dB, dBm to 0.01 dB resolution. A separate reference for each λ can be stored and displayed.

Tight total uncertainty specifications cover the entire measuring range, operating temperatures, connector types and fiber types. Calibration is ISO 17025 traceable.

The handy tone detector is a useful craft aid for fiber identification. The actual modulation frequency is measured and displayed, so that source modulation frequencies can be checked.

For fiber optic specific versions of this power meter, or for general features of a particular instrument range, please refer to the general KI2600 & KI9600 brochures. Please see other brochures for matching light sources, or complete inspection & test kits.

Additional general features of the premium KI2600XL range include: more calibration wavelengths, high power capability, external power & charging, captive dust cover for optical connector, larger display, memory, USB key data dump, text naming, computer interface & software featuring live data logging or reporting in multiple languages.

Please see other brochures for POF or MPO applications for these power meters, other versions of these power meters, matching light sources, or complete inspection & test kits.

Please enquire for non-standard calibration wavelengths or connector styles.

SPECIFICATIONS

Response λ, nm	Damage level dBm	Calibration λ nm	Power range dBm	Tone & Autotest Min dBm ⁵	Mid range linearity dB ¹	Calibration Accuracy % ²	Polarization Sensitivity dB ⁶	Total Uncertainty dB ^{3,5}	λ Sensitivity ± 30 nm dB ⁵	Response uniformity across detector
<i>KI 2600H3BXL-InGaAs2 (filtered 2 mm InGaAs detector):</i>										
800 ~ 1700	+35 ⁴	850, 980,1270,1300,1310,1330,1350, 1370,1390,1410,1430,1450,1470, 1490,1510,1530,1550,1570,1590, 1610,1625,1650	+33 ~ -30 +33 ~ -40	-25	0.04	1 % (0.06 dB)	< 0.05	0.35	0.03	1 % (0.06 dB)
<i>KI 2600H3BXL-Ge2 (filtered 2 mm Ge detector):</i>										
600 ~ 1650	+35 ⁴	780,820,850,1590,1610,1625,1650 980,1270,1300,1310,1330,1350, 1370,1390,1410,1430,1450,1470, 1490,1510,1530,1550,1570	+33 ~ -30 +33 ~ -40	-20	0.06	1 % (0.06 dB)	< 0.05	0.5	0.04	2 % (0.09 dB)
<i>KI 2600XL-InGaAs5 (5 mm InGaAs detector):</i>										
600 ~ 1700	+15	780, 820, 850, 880, 910, 940 980,1270,1300,1310,1330,1350, 1370,1390,1410,1430,1450,1470, 1490,1510,1530,1550,1570,1590, 1610,1625,1650	+70 ~ -50 +10 ~ -60	-40	0.04	1 % (0.06 dB)	< 0.05	0.35	0.03	1 % (0.06 dB)
<i>KI 2600XL-Ge5 (5 mm Ge detector):</i>										
600 ~ 1650	+20	635,650,660,780,820,1590,1610,1625,1650, 850,880,910,940,980,1270,1290,1300, 1310, 330,1350,1370,1390,1410,1430, 1450,1470,1490,1510,1530,1550,1570	+15 ~ -30 +15 ~ -40	-37	0.06	1 % (0.06 dB)	< 0.05	0.5	0.03	2 % (0.09 dB)
<i>KI 2600XL-Ge7 (7 x 3.5 mm Ge detector):</i>										
600 ~ 1650	+20	635,650,660,780,820,1590,1610,1625,1650, 850,880,910,940,980,1270,1290,1300, 1310,1330,1350,1370,1390,1410,1430, 1450,1470,1490,1510,1530,1550,1570	+15 ~ -30 +15 ~ -40	-30	0.06	1 % (0.06 dB)	< 0.05	0.5	0.03	2 % (0.09 dB)
<i>KI 9600XL-Ge5 (5 mm Ge detector):</i>										
600 ~ 1650	+15	635,650,660,780,1610,1625 850,1300,1310,1390,1490,1550	+70 ~ -30 +10 ~ -40	-37	0.06	2 % (0.09 dB)	< 0.05	0.5	0.04	2 % (0.09 dB)
<i>KI 9600XL-Ge7 (7 x 3.5 mm Ge detector):</i>										
600 ~ 1650	+15	635,650,660,780,1610,1625 850,1300,1310,1390,1490,1550	+70 ~ -30 +10 ~ -40	-30	0.06	2 % (0.09 dB)	< 0.05	0.5	0.04	2 % (0.09 dB)
<i>KI 2600XL-Si5 (5 mm Si detector):</i>										
350 ~ 1100	+15	400,430,470,490,520,550,580, 600,635, 650,660,670,700,740,780,820,850, 880,910,940,980	+70 ~ -50 +10 ~ -60	-45	0.04	1 % ⁷ (0.06 dB)	< 0.05	0.3	0.03	1 % (0.06 dB)
<i>KI 9600XL-Si5 (5 mm Si detector):</i>										
350 ~ 1100	+10	470,520 635,650,660,780,820,850,980	+5 ~ -50 +5 ~ -60	-45	0.02	2 % (0.09 dB)	< 0.05	0.3	0.03	1 % (0.06 dB)

	Typical	typical	typical	max	typical
--	---------	---------	---------	-----	---------

Note 1: Mid-range linearity @ 1550 nm for InGaAs & Ge, or 850 nm for Si. Non-coherent light, with APC connector. Excludes top 5 dB and bottom 10 dB of range.

Note 2: Calibration condition: non-coherent light, -35±5 dBm, 23±3°C, ±1 nm, 10±3 nm FWHM, PC ceramic connector, 100 µm fiber.

Note 3: Includes contributions of: varying optical connector types, calibration uncertainty, linearity over temperature & range fiber core diameter up to 1 mm (for 2 mm detector, max NA = 0.3) or , fiber core diameter up to 1 mm (for 5 mm detector, max NA= 0.5) or fiber core diameter up to 3 mm (for 5 mm detector, max NA= 0.3).

Note 4: H3B can sustain the damage level for 2 minutes.

Note 5: At calibration wavelengths in bold type.

Note 6: For APC connectors only.

Note 7: 400, 430 nm are 4% (0.2 dB) accuracy

GENERAL SPECIFICATIONS

Parameters	KI 2600	KI 9600
Battery life	Up to 1000 hours	300 hours
Size / Weight	190 x 165 x 38 mm (7.5 x 6.5 x 1.5") / 420 gm (0.9 lb.)	124 x 81 x 25 mm (4.9 x 3.2 x 1.0") / 150 gm (0.33 lb.)
Operating / Storage	15 to 55 °C / -25 to 70 °C	-15 to 55 °C / -25 to 70 °C
Relative humidity	0 ~ 95 %	0 ~ 95 %
Warranty	3 years	3 years
Recommended calibration cycle	3 years	3 years
Case	Polycarbonate / rubber edges & corners, moisture resistance, 1-meter drop tested	Polycarbonate / rubber edges & corners, moisture resistance, 2.5 meters drop tested
Dust cap	Captive, functions as tilt bail when slid open	(use connector adaptor)
Tone detection	150 ~ 9900 Hz ± 1 %	200 ~ 2500 Hz ± 2 %
Max / Min	Recording feature for stability testing	Recording feature for stability testing
Power	2x Alkaline / Lithium AA cells or 2x NiMH AA cells, user selectable charging; Ext power input via micro USB; Selectable auto-off, low battery indicator, backlit display	2x alkaline / Lithium AAA cells. Selectable auto-off, low battery indicator
Memory	1000 four-λ tests with date & time in internal memory, unlimited on USB memory key	N/A (display hold)
USB interfaces	Micro-USB for general USB & power; USB-A type connector for memory key only	N/A

FEATURE AND APPLICATION COMPARISON

5 mm Ge and InGaAs Detector Power Meters:				
Feature	Typical Application	KI 2600XL-Ge5	KI 2600XL-InGaAs5	KI 9600XL-Ge5
Autotest	Simultaneous multi- λ Loss test	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
USB / KITS™ software	Data acquisition, pass /fail, computer display	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
External Power		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Backlight		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
5 mm Ge or InGaAs	Most connector styles, Max fiber exit diameter for NA= 0.2: 3 mm	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Power range		+15 ~ -40 dBm	+10 ~ -60 dBm	+10 ~ -40 dBm
Response Range		600 ~ 1650 nm	600 ~ 1700 nm	600 ~ 1650 nm
POF calibration λ		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
MMF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

7 x 3.5 mm Ge Detector Power Meters:		
Feature	Typical Application	KI 2600XL-Ge7
Autotest	Simultaneous multi- λ Loss test	<input checked="" type="checkbox"/>
USB / KITS™ software	Data acquisition, pass /fail, computer display	<input checked="" type="checkbox"/>
External Power		<input checked="" type="checkbox"/>
Backlight		<input checked="" type="checkbox"/>
7 mm Ge	Most connector styles Max fiber exit diameter for NA = 0.2: 1 x 5 mm	<input checked="" type="checkbox"/>
Power range		+15 ~ -40 dBm



Response Range	600 ~ 1650 nm		
POF calibration λ	<input checked="" type="checkbox"/>		
MMF calibration λ	<input checked="" type="checkbox"/>		
SMF calibration λ	<input checked="" type="checkbox"/>		
2 mm High Power Detector Power Meters:			
Feature	Typical Application	KI 2600H3BXL-Ge2	KI 2600H3BXL-InGaAs2
Autotest	Simultaneous multi- λ Loss test	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
USB / KITS™ software	Data acquisition, pass /fail, computer display	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
External Power		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Backlight		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2 mm Ge or InGaAs	Single core SMF / MMF with very high power levels	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Power range		+33 ~ -40 dBm	+33 ~ -40 dBm
Response Range		600 ~ 1650 nm	800 ~ 1700 nm
POF calibration λ		<input checked="" type="checkbox"/>	
MMF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5 mm Silicon Detector Power Meters:			
Feature	Typical Application	KI 2600XL-Si5	KI 9600XL-Si5
Autotest	Simultaneous multi- λ Loss test	<input checked="" type="checkbox"/>	
USB / KITS™ software	Data acquisition, pass /fail, computer display	<input checked="" type="checkbox"/>	
External Power		<input checked="" type="checkbox"/>	
Backlight		<input checked="" type="checkbox"/>	
5 mm Si	Most connector styles Max fiber exit diameter for NA= 0.2: 3 mm. POF = 1 mm diameter	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Power range		+10 ~ -60 dBm	+5 ~ -60 dBm
Response Range		350 ~ 1100 nm	350 ~ 1100 nm
POF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MMF calibration λ		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

ORDERING INFORMATION

To order Power Meter, please specify:

- 1) Instrument part number
- 2) At least one interchangeable adaptor
- 3) Accessories as required.

Description	Part number
Instrument, Power Meter Ge 5mm	KI 2600XL-Ge5
Instrument, Power Meter Ge 5mm	KI 9600XL-Ge5
Instrument, Power Meter InGaAs 5mm	KI 2600XL-InGaAs5
Instrument, Power Meter H3B Ge 2mm	KI 2600H3BXL-Ge2
Instrument, Power Meter H3B InGaAs 2mm	KI 2600H3BXL-InGaAs2
Instrument, Power Meter Si 5mm	KI 2600XL-Si5
Instrument, Power Meter Si 5mm	KI 9600XL-Si5
Instrument, Power Meter Ge 7mm	KI 2600XL-Ge7
Instrument, Power Meter Ge 7mm	KI 9600XL-Ge7

Please enquire for non-standard specifications.

STANDARD ACCESSORIES

Description	Quantity	
	KI 2600	KI 9600
Operating manual / Quick guide	1	1
QA certificate	1	1
ILAC/ NATA traceable Calibration certificate	1 set	1 set
Soft carry pouch	1	1
Wrist strap	1	1
USB cable (A-micro type)	1	-
KITS™ Recording/reporting software	Download from website for free	

OPTIONAL ACCESSORIES

Description	Part number
Option, Carry Case, KI2x/KI7x/KI3x, small (Carry Case for 2 Instruments)	OPT153*
Option, Carry Case, Cletop, Cleaning Sticks, KI2x / KI9x, large	OPT154B*

Please visit kingfisherfiber.com for a wide range of FiberTester kits.

OPTIONAL INTERCHANGEABLE CONNECTOR ADAPTORS

Description	Part number	Description	Part number
Option, Connector Adaptor XL 7/8-28, SC	OPT201	Option, Connector Adaptor XL 7/8-28, MT ferrule	OPT232
Option, Connector Adaptor XL 7/8-28, ST	OPT202	Option, Connector Adaptor XL 7/8-28, Senko CS	OPT200 ⁸
Option, Connector Adaptor XL 7/8-28, LC	OPT226A	Option, Connector Adaptor XL 7/8-28, SMA 905/906	OPT203
Option, Connector Adaptor XL 7/8-28, FC	OPT204	Option, Connector Adaptor XL 7/8-28, POF multi	OPT229 ⁹
Option, Connector Adaptor XL 7/8-28, 1.25 mm Universal	OPT224	Option, Connector Adaptor XL 7/8-28, POF SC	OPT201-POF
Option, Connector Adaptor XL 7/8-28, 2.5 mm Universal	OPT225	Option, Connector Adaptor XL 7/8-28, POF ST	OPT202-POF
Option, Connector Adaptor XL 7/8-28, Toslink	OPT230	Option, Connector Adaptor XL 7/8-28, POF FC	OPT204-POF
Option, Connector Adaptor XL 7/8-28, Biconic	OPT205	Option, Connector Adaptor XL 7/8-28, POF 2.5 mm universal	POF225-POF
Option, Connector Adaptor XL 7/8-28, MTP / MPO 12 x n	OPT227 ⁷	Option, Connector Adaptor XL 7/8-28, HFBR	OPT231
Option, Connector Adaptor XL 7/8-28, MTP / MPO 16 x n	OPT228 ⁸		

Adaptors are suitable for both PC and APC polish connectors. Other styles available on request. For use with POF fiber, adaptors with a pinhole at the connector tip will need the pinhole to be drilled out.

Note 7: Suitable for instrument with 5 mm (-Ge5, -InGaAs5, -Si5) or 7x3.5 mm (-Ge7) detector.

Note 8: Suitable for instrument with 7x3.5 mm (-Ge7) detector only.

Note 9: Suitable for Mini Toslink, unterminated POF cable, HFBR series (simplex and duplex), 2.5mm. The user turns the turret to the required hole size. Actual hole size 3.85, 3.5, 3.2, 2.55, 2.4, 2.3 mm x 8.5 mm deep. Not suitable for SMA connectors, use OPT203 for SMA instead.



AUTHORIZED DEALER